

PRECAUTIONARY STATEMENTS

CAUTION: IRRITANT. CAUSES EYE IRRITATION. HARMFUL IF SWALLOWED. CONTAINS CALCIUM CHLORIDE.

Do not get in eyes or on skin. Do not breathe dust. Wear goggles or safety glasses with side shields and rubber gloves when handling this product. Wash thoroughly after handling. Do not mix with other chemicals.

FIRST AID:

If Swallowed

- Call poison control center or doctor immediately for treatment advice.
- Do not induce vomiting unless told to do so by the poison control center or doctor.
- Do not give anything by mouth to an unconscious person.

If in Eyes

- Hold eye open and gently rinse with water for 15-20 minutes.
- Remove contact lenses, if present, after first 5 minutes, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

If on Skin or Clothing

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or doctor for treatment advice.

If Inhaled

- Move person to fresh air.
- Call a poison control center or doctor for further treatment advice.

Have the product container or label with you when calling a poison control center or doctor or going for treatment.

Storage and Disposal: Keep product dry in the original, tightly closed container when not in use. Store in a cool, dry, well ventilated area. Keep out of reach of children. **Container Disposal:** Do not reuse empty container. Rinse empty container thoroughly with water then place in trash collection or offer for recycling, if available.



Calcium +

Increases calcium hardness level to prevent corrosion

Active Ingredients: Calcium Chloride

**KEEP OUT OF REACH OF CHILDREN
CAUTION**

See First Aid and Additional Precautionary Statements on Back Panel.

Net Weight 4 LBS.

DIRECTIONS FOR USE:

Read entire label and use strictly in accordance with precautionary statements and directions.

This product is used to raise calcium hardness in swimming pool water. Low calcium hardness may cause pool water to become corrosive which can result in etched plaster, corrosion of equipment and fixtures or may cause metallic stains. The ideal range is 200 to 400 parts per million (ppm). The minimum calcium hardness level is 150 ppm.

1. Test water for hardness.
2. If calcium hardness is below 200 ppm, determine the dosage of this product from the table below.
3. Broadcast product over the surface of the water while the pump is running. Do not predissolve this product.
4. Do not add this product on the same day that either ph plus or alkalinity increaser has been added to the pool water.

Pool Volume in Gallons	To increase hardness 50 ppm	To increase Hardness 100 ppm	To increase Hardness 200 ppm
2,000	1.5 lbs.	3 lbs.	6.25 lbs.
5,000	3 lbs.	6.25 lbs.	12.5 lbs.
10,000	6.25 lbs.	12.5 lbs.	25 lbs.
20,000	10.5 lbs.	25 lbs.	50 lbs.

Sold By:
CINDERELLA, INC.
Saginaw, MI 48601



0 1 2 7 7 5 4 5 5 0 4 6